

DECKfon® Batten 45 & 70

Resilient Composite Acoustic Battens



Product Information

DECKfon acoustic battens consist of a layer of recycled, low resonance, open-cell, flexible polyurethane foam bonded to a FSC® / PEFC® certified timber batten. They have been rigorously tested, and are Robust Detail compliant for steel, concrete & timber separating floor applications.

Product Benefits

- Outstanding acoustic performance
- Two types available: 45mm and 70mm high*
- Suitable for all floor types
- Robust Detail **FFT1** and **3** compliant
- FSC® / PEFC® certified timber

Technical Information

		DECKfon	
		Batten 45	Batten 70
Product description	-	Resilient composite shallow batten	Resilient composite deep batten
Design height (when loaded to 25kg/m²)	mm	45	70
Pre-loaded height	mm	50	75
Batten dimensions	mm	45 (wide) x 2400 (long)	45 (wide) x 2400 (long)
Resilient layer	-	10mm open-cell polyurethane foam	10mm open-cell polyurethane foam
Weight	kg/lm kg/length	0.80 1.90	1.57 3.75
Associated flanking strip required	-	YELOfon ES5/100	YELOfon ES5/120

Third Party Accreditation and Approvals



Environmental Credentials

"Look for FSC Certified Products"

