

FIBREfon[®] 12C, 21C & 28C

Composite Acoustic Overlay Floorboards for Concrete Floor Applications



Product Information

FIBREfon shallow platform floating floor treatments are Robust Detail **FFT 5** compliant, with their acoustic performance third party tested. All three treatments combine a tongue and groove timber floorboard with a high compressive strength resilient layer.

Product Benefits

- Excellent acoustic performance - **RD FFT 5** compliant
- Three thickness' available: 12, 21 & 28mm
- Moisture resistant T & G floorboard
- High compressive strength resilient layer
- Quick and easy to install

Technical Information

		FIBREfon		
		12C	21C	28C
Product description	-	Composite acoustic overlay floorboard	Composite acoustic overlay floorboard	Composite acoustic overlay floorboard
Overall thickness	mm	12	21	28
Type of facing board	-	9mm MR MDF	18mm P5 Chipboard	18mm P5 Chipboard
Resilient layer	-	3mm fleece	3mm fleece	10mm woodfibre
Board dimensions	mm	600 x 2400	600 x 2400	600 x 2400
Weight	kg/m ² kg/board	6.95 11.00	13.10 18.88	14.10 20.30
Associated flanking strip required	-	YELOfon FS15	YELOfon FS30	YELOfon FS30

Third Party Accreditation and Approvals



Environmental Credentials

