

## HiGYP® 30TM & FIBREfon® Baffle strips

High Performance Acoustic Composite Wall Boards & Acoustic Baffle Strips



### Product Information

CELLECTA's HiGYP 30TM acoustic wall lining treatment dramatically reduces airborne sound transmission through and down all types of masonry walls, with timber joist separating floors, by isolating the lining boards from the structural wall with patented acoustic FIBREfon Baffle Strips.

### Product Benefits

- ⬢ Outstanding acoustic performance
- ⬢ Only 45mm overall thickness (30mm + 15mm)
- ⬢ Suitable for timber floors supported by masonry walls
- ⬢ Provides 15mm cavity to run services within
- ⬢ Patented system

### Technical Information

		HiGYP	FIBREfon
		30TM	Baffle strips
Product description	-	Acoustic composite wall lining board with high density facing	Sound absorbing, void forming baffles
Overall thickness'	mm	30	15
Type of facing board	mm	15mm thick high density gypsum	N/A
Resilient layer	mm	15mm thick LD woodfibre board	15mm thick LD woodfibre board
Dimensions	-	1200 x 2400	75 x 1200 (8 strips/30TM board)
Weight	kg/m <sup>2</sup> kg/unit	14.90 42.91	- 0.216
Associated flanking strip required	-	CELLECTA C-strip	N/A

### Third Party Accreditation and Approvals



### Environmental Credentials



\*Pre-completion testing require prior to full Robust Detail status being awarded.



01634 29-66-77



collecta.co.uk



technical@collecta.co.uk