CELLECTA HP30

High Performance Ceiling Resilient Bars

Product Information

HP30 deep resilient bars virtually decouple the ceiling from the floor joists, and deliver superior acoustic performance over standard resilient bars. The bar's double fixing flanges allows high mass plasterboards to be installed, often eliminating the need for a secondary ceiling

Product Benefits

- Superior acoustic performance and hanging capabilities than 16mm resilient bars
- RD proprietary component for **E-FS-3, E-FT-5 & E-FT-6**
- Reduces risk of screws causing acoustic bridging
- Only need to be installed at 600mm centres

Technical Information

		HP30	Standard resilient bar
Product desciption	-	High performance resilient ceiling bar	Metal resilient bar
Depth	mm	**30**	**16**
Length	mm	3000	3000
Number of fixing flanges	-	2	1
Max hanging weight: Joists at 450mm centres	Kg/m²	**59** @450mm centres **48** @600mm centres	**50** @450mm centres -
Joists at 600mm centres	Kg/m²	**48** @450mm centres **36** @600mm centres	**40** @450mm centres -
Associated flanking strip required	-	CELLECTA **C-strip**	

Third Party Accreditation and Approvals

RD Proprietary Component

NHBC LABC warranty Premier Guarantee Accepted

BMTRADA ISO 9001: 2015

SRL Performance Tested