

RUBBERfon[®] ULTRAtop 3 & 5

Acoustic Coverings for Concrete Floors



Product Information

RUBBERfon Ultratop cork/rubber composite acoustic floor covering is the ideal barrier to address impact sound transmission on floors where either a LVT, vinyl, wooden flooring or tiling are to be applied directly on the acoustic treatment.

Product Benefits

- ⊕ Excellent impact sound reduction
- ⊕ Available in two thickness': 3 & 5*mm
- ⊕ Robust Detail **E-FC-8*** compliant
- ⊕ Made from high compressive strength recycled rubber
- ⊕ Compatible with all types of floor finish, inc ceramic tiles

Technical Information

		RUBBERfon	
		Ultratop 3**	Ultratop 5*
Product description	-	Direct to joist, two layer composite acoustic structural floorboard	Direct to joist, four layer composite acoustic structural floorboard
Overall thickness	mm	3	5
Roll dimensions	m	1 x 15	1 x 10
Coverage	m ²	15	10
Density	m ³	750	750
Weight	kg/m ² kg/roll	750 33.75	750 37.50
Adhesive required to bond to floor structure	-	CELLECTA UL80 adhesive	CELLECTA UL80 adhesive

Third Party Accreditation and Approvals



Environmental Credentials



*Pre-completion testing require prior to full Robust Detail status being awarded.